## INQUIRY:

Product:  ☐ Standard ☐ Modification of standard product ☐ Co	ustom integrated platform		
Dimensions:			
H x W x D:HP xmm			
Number of slots:			
slots			
Card depth: 160mm I/O configuration: N	one 🗆 80mm		
CompactPCI backplane:			
59 as heread William and the many files	v		
slots			
PICMG version:			
☐ 32bit ☐ 66 bit			
□ Standard			
Customization:			
Power supply:			
☐ ATX type ☐ cPCI plug in			
Input voltage:   AC/V   DC/V			
Output voltage and currents:			
□ +3.3V /A □ +5.0V /A □ +12V /A			
□-12V/A □V/A			
Ventilation:			
☐ Fixed fan ☐ Hot-swappable Fan tray			
Air entry:  Bottom Top Front Rear Right Left			
Air exit:			
Fan filter:  Yes  No			
Device holder:			
☐ 3.5" x (number)			
☐ 5.25" x (number)			
others:			
Finish:			
□ Chromate □ Painted: color □ Other:			
Other Requirements www.mapsuka.com.t			.tw
	Fax	: + 8 8 6 - 2 - 2 2 6 9 0 3	3 2 7
Quantities:	units		
Address			
Name	Job title		
Company	Department		
Web	Email		
Tel	Fax		
2.50			
Address			